



DESIGN | ORIGINALITY | EXPERTISE



IPE WOOD MAINTENANCE

IPE HARDWOOD MAINTENANCE INSTRUCTIONS

Ipe is a strong and durable exotic hardwood that is naturally resistant to rot and decay. When allowed to weather over time, Ipe hardwood will turn a beautiful silvery-gray similar to teak. To return to its original luster and extend the life of your products, we recommend Ipe Oil™. It is specially formulated to replenish the look of weathered hardwoods. This will provide a fast and easy way to improve the appearance of your products while offering excellent protection against harmful UV rays.

HOW TO APPLY IPE OIL™ ON YOUR PRODUCTS

- Remove dirt and debris from the wood surface & in between gaps.
- Pre-rinse hardwood with a hose.
- Wait until the surface is completely dry (at least 24 hours in most areas).
- Use a paint roller or paint brush to apply.
- Using a dry rag, rub in any excess or pooled liquid that remains after 5 minutes.
- Let dry completely.
- Properly dispose of can and rags - Do NOT leave cans & used rags exposed to the elements.

FOR BEST RESULTS:

Avoid applying:

- Under full sun
- If rain is forecast within 24 hours
- In extreme hot or cold temperatures
- More than once per season



PICTURED:
Volant 6' Bench with Back

PROPRIETARY STATEMENT

This document and all information shown hereon are the exclusive property of Keystone Ridge Designs, Inc.® This document is furnished with the express understanding that neither it nor the information on it is to be disclosed or

reproduced in whole or in part, or used in any way, either directly or indirectly, for the benefit of anyone other than Keystone Ridge Designs, Inc.® without its written consent.



670 Mercer Road | Butler, PA 16001-1840
Toll-free: 1-800-284-8208 | Phone: 724-284-1213 | Fax: 724-284-1253
www.keystoneridgedesigns.com